



FA1 - i.MX27 implementation + LTIB

This course describes the i.MX27 multimedia processor and Linux Target Image Builder tool

Objectives

- The course details the hardware implementation of the i.MX27 microcontroller.
- The boot sequence and the clocking are explained.
- The course explains all parameters that affect the performance of the system in order to easily perform the final tuning.
- A description of all internal peripherals is provided.
- An overview of the ARM926EJ-S core helps to understand issues caused by cache and MMU.
- The course ends with practical labs explaining how to generate a Linux image as well as a Root File System, by using a tool called LTIB [Linux Target Image Builder].
- This course has been delivered to several companies developing multimedia equipments.

A lot of programming examples have been developed by ACSYS to explain the boot sequence and the operation of complex peripherals.

-They have been developed with GNU compiler and are executed under Lauterbach debugger.

-Furthermore, a host desktop running Fedora Linux is used to generate Linux image and Root File System during labs on LTIB.

A more detailed course description is available on request at info@ac6-training.com

Prerequisites

- This course provides an overview of the ARM926 core. Our course reference [R1](#) details the operation of this core.
- The following courses could be of interest:
 - USB Full Speed High Speed and USB On-The-Go, reference [IP2](#)
 - Ethernet and switching, reference [N1](#)

Plan

ARCHITECTURE OF i.MX27

Overview

- ARM core based architecture
- Clarifying the internal data paths
- Highlighting the purpose of the 2 central interconnect units : MAX and M3IF
- Organization of a board based on i.MX27

■ Mapping

CORE PLATFORM**THE ARM926EJ-S CORE**

- Presentation of the core
- Operating modes
- Pipeline
- ARM vs Thumb instruction sets, interworking
- Branch instructions
- C-to-Assembly interface
- Exception mechanism
- Debug facilities

THE ARM9 PLATFORM

- AHB slave device latencies
- MAX parameterizing
- ARM Interrupt Controller [AITC]

HARDWARE IMPLEMENTATION**RESET AND CLOCKING**

- Clock distribution
- Power-up sequence
- Low power modes, clock gating
- System boot mode selection
- Bootstrap mode operation

SYSTEM CONTROL

- GPIO module
- General Purpose Input interrupt request capability
- Signal description

ACCESSING EXTERNAL MEMORIES

- Description of the Master Arbitration and Buffering [MAB] unit
- Description of the M3IF arbitration [M3A]
- Enhanced DDR SDRAM controller
- NAND flash controller, boot from flash
- Programming the chip-selects

STANDARD PARALLEL INTERFACES

- ATA controller
- PIO mode
- Ultra DMA mode
- FIFO receive and FIFO transmit alarms
- MSHC
- Transfer protocol
- Error management

- SDHC
- Interface to SD cards
- Transfer protocol
- Error management

MULTIMEDIA UNITS

DMA CONTROLLER

- Channel priority definition
- Burst length definition
- 2D memory transfers
- Double-buffering mechanism enabling chained transfers

VIDEO PROCESSING UNITS

- Video acquisition
- CSI interface
- Configuring the interface to support CCIR656
 - Video pre-processor
- Image resizing
- Color space conversion
 - Video post-processor
- Deblock
- Dering
- Image resizing
- Color space conversion
 - Video codec
- MPEG-4 encoding / decoding
- H.264 AVC encoding / decoding

AUDIO RELATED INTERFACES

- SSI interfaces
- Connection of Codecs or DSPs
- AC97 support
 - Digital audio multiplexor
- Connecting host interfaces to peripheral interfaces
- Internal network mode

SECURITY MODULES

- Security Controller
 - SAHARA2 security coprocessor
- Random number generator
- Encryption / decryption sequences
 - Run-Time Integrity Checker
- SHA-1 message authentication
- Segmented data gathering
 - IC Identification Module

COMMUNICATION CONTROLLERS

- 1-wire interface
- Configurable SPI
- SPI protocol basics

- Master / slave operation
- Transfer sequence
 - I2C interfaces
- I2C protocol basics
- Master vs slave
- Transfer sequence
 - UART
- IrDA modulation / demodulation
- Support for Smart Card
- Flow control
 - USB
- Explaining what is OTG
- High-speed operation
- EHCI support
- Full speed operation
- Endpoint configuration
 - Fast Ethernet Controller [FEC]
- Buffer management, based on Buffer Descriptors
- Incoming frame filtering mechanisms
- VLAN support

LCD CONTROL

- LCDC
- LCD screen format
- Standard panel interface for common LCD drivers
- Graphic window on screen
 - SLCDC
- Interface to an external display controller
- Transferring images and controls from DDR to the external controller

LTIB

GENERATING THE LINUX KERNEL IMAGE

- What is required on the host before installing LTIB
- Common package selection screen
- Common target system configuration screen
- Building a complete BSP with the default configurations
- Creating a Root Filesystems image
- Re-configuring the kernel under LTIB
- Selecting user-space packages
- Setup the bootloader arguments to use the exported RFS
- Debugging Uboot and the kernel by using Trace32
- Adding a new package
- Other deployment methods
- Creating a new package and integrating it into LTIB

Renseignements pratiques

Duration : 4 days
Cost : 1500 € HT