



This course covers NXP MPC8641 and MPC8641D single- and dual- core Power CPUs

Objectives

- The course clarifies the architecture of the MPC8641D, particularly the operation of the coherency module that interconnects the e600s to memory and high-speed interfaces.
- Cache coherency protocol is introduced in increasing depth.
- The e600 core is viewed in detail, especially the AltiVec units that enable vector processing.
- The boot sequence and the clocking are explained.
- The course focuses on the hardware implementation of the MPC8641D.
- A long introduction to DDR SDRAM operation is done before studying the DDR SDRAM controller.
- An in-depth description of the RapidIO port and the PCI-Express port is done.
- The course highlights both hardware and software implementation of gigabit / fast / Ethernet controllers.

A more detailed course description is available on request at formation@ac6-formation.com

Prerequisites and related courses

- Experience of a 32-bit processor or DSP is mandatory.
- Knowledge of the RapidIO (see our cours [IC5 - RapidIO 3.0](#)) and PCI Express bus (see our cours [IC4 - PCI Express 3.0](#)) is recommended.

Environnement du cours

- Cours théorique
 - Support de cours au format PDF (en anglais) et une version imprimée lors des sessions en présentiel
 - Cours dispensé via le système de visioconférence Teams (si à distance)
 - Le formateur répond aux questions des stagiaires en direct pendant la formation et fournit une assistance technique et pédagogique
- Au début de chaque demi-journée une période est réservée à une interaction avec les stagiaires pour s'assurer que le cours répond à leurs attentes et l'adapter si nécessaire

Audience visée

- Tout ingénieur ou technicien en systèmes embarqués possédant les prérequis ci-dessus.

Modalités d'évaluation

- Les prérequis indiqués ci-dessus sont évalués avant la formation par l'encadrement technique du stagiaire dans son entreprise, ou par le stagiaire lui-même dans le cas exceptionnel d'un stagiaire individuel.
- Les progrès des stagiaires sont évalués par des quizz proposés en fin des sections pour vérifier que les stagiaires ont assimilé les points présentés
- En fin de formation, une attestation et un certificat attestant que le stagiaire a suivi le cours avec succès.
 - En cas de problème dû à un manque de prérequis de la part du stagiaire, constaté lors de la formation, une formation différente ou complémentaire lui est proposée, en général pour conforter ses prérequis, en accord avec son responsable en entreprise le cas échéant.

Plan

MPC8641D OVERVIEW

Overview

- e600 core, usage of a dual core device
- Coherency Module
- Examples of data flow through the MPC8641D
- Address map, local access windows
- Outbound and inbound address translation windows

e600 CORE

PIPELINE

- Pipeline basics
- Introduction to e600 pipeline
- e600 pipeline implementation
- Execution serialization, purpose of the isync instruction
- Branch management
- Guarded memory
- Coding guidelines
- Performance monitor

INTERNAL DATA AND INSTRUCTION PATHS

- L1 and L2 cache loading, hit under miss
- The MSS [Memory Sub System]
- The load fold queue
- The store miss merging advantage when several vectors must be stored
- The BIU [Bus Interface Unit]
- Purpose of sync and eieio instructions

L1 AND L2 CACHES

- Cache basics
- e600 L1 cache : PLRU algorithm, HID0/ICTRL programming interface, way locking
- L1 data cache flush
- Transient load instructions benefits
- L2 cache organization
- L2 replacement algorithm selection, L2 locking
- Cache coherency basics
- MESI snooping sequences involving 2 e600s and a PCI Express master

e600 PROGRAMMING

- User and supervisor registers
- The system call communication path between applications and RTOS
- Integer load / store instructions, boolean semaphore management
- IEEE754 basics
- FPU operation : FPSCR register, IEEE vs non-IEEE mode
- The EABI
- Code and data sections, small data areas benefits

ALTIVEC

- AltiVec introduction, SIMD processing
- Intra vs inter element instructions
- AltiVec registers, VSCR initialization
- ANSI C extension to support vector operators, new C types, new castings, vector declaration and initialization
- AltiVec implementation on the e600 : the VALU and the VPU execution units
- Data streams management
- EABI extension to support AltiVec

THE MEMORY MANAGEMENT UNIT

- MMU goals
- Enabling 4 additional BATs
- 32-bit or 36-bit real address size selection
- WIMG attributes definition, page and block access rights definition
- Page protection through VSID selection
- TLB organization, TLB software management
- Page translation : PTEG selection, tablesearch, PTE content
- Software vs hardware TLB reload
- MMU implementation in real-time sensitive applications

THE EXCEPTION MECHANISM

- Exception state saving and restoring through SRR0/SRR1 registers
- Exception management
- Recoverable vs non recoverable interrupts
- Requirements to support exception nesting
- Performance monitor

MPC8641D INFRASTRUCTURE

RESET AND CLOCKING

- Platform clock
- RapidIO transmit clock source selection
- Power-on reset sequence, use of the I2C interface to access a serial ROM
- Power-on reset configuration
- Boot page translation

MPX COHERENCY MODULE

- I/O arbiter
- MPX arbiter
- Transaction queue
- Global data multiplexor
- MPX interface

MULTIPROCESSOR PERIPHERAL INTERRUPT CONTROLLER

- Open PIC architecture compatibility
- Interrupt nesting
- Description of the 4 timers / counters
- Message interrupts
- e600-to-e600 interrupt capability

DDR-SDRAM MEMORY CONTROLLER

- DDR2 operation
- Command truth table
- Hardware interface
- Refresh types
- Bank activation, read, write and precharge timing diagrams, page mode
- ECC error correction
- Initial configuration following Power-on-Reset
- Address decode
- Timing parameters programming
- FCRAM interface commands

LOCAL BUS CONTROLLER

- Multiplexed 32-bit address and data transfers
- Burst support
- Dynamic bus sizing
- GPCM, UPMs and SDR SDRAM states machines

INTEGRATED DMA CONTROLLER

- Priority between the 4 channels
- Support for cascading descriptor chains
- Scatter / gathering
- Selectable hardware enforced coherency
- Ability to start DMA from external 3-pin interface

SERIAL RapidIO INTERFACE

- Message Unit, direct vs chaining mode operation
- RapidIO doorbell and port-write unit
- Accessing configuration registers via RapidIO packets
- Programming inbound and outbound ATMUs
- Error handling

PCI EXPRESS INTERFACE

- Modes of operation, Root Complex / Endpoint
- Byte swapping
- Transaction ordering rules
- Programming inbound and outbound ATMUs
- Configuration, initialization

PERFORMANCE MONITOR AND DEBUG FEATURES

- Event counting
- Threshold events
- Watchpoint facility
- Trace buffer

MPC8641D INPUT / OUTPUT PERIPHERALS

THE ETHERNET CONTROLLERS

- 802.3 specification fundamentals : the 3 layers PHY, MAC and control
- Frame format with and without VLAN option
- Address recognition, pattern matching
- Buffer descriptors management
- The enhanced three-speed Ethernet controllers (eTSECs)
- Physical interfaces : GMII, MII, TBI or RGMII

- Buffer descriptor management
- Layer 2 acceleration accept or reject on address or pattern match
- 256-entry hash table for unicast and multicast
- IPv4, TCP and UDP checksum verification and generation
- Quality of service support

I2C CONTROLLERS

- I2C protocol fundamentals : addressing, multimaster operation
- Transmit and receive sequence

SERIAL INTERFACE

- Introduction to UART protocol
- Description of the NS16450/16550 compliant Uarts
- Flow control signal management

Renseignements pratiques

Renseignements : 5 jours