



## This course PowerQUICC II devices, such as MPC8247

### Objectives

- The course describes various implementation of the MPC824X: PCI host and PCI IO device.
- The course details the address translation mechanism used to access from core to PCI and from PCI to SDRAM.
- The course focuses on low level programming and EABI understanding.
- The hardware implementation is studied, particularly the SDRAM controller.
- The course explains the scatter / gather operation of the DMA channel.
- Synchronization between masters through message is highlighted.

*A lot of programming examples have been developed by ACSYS to explain the boot sequence and the operation of complex peripherals, such as PCI bridge and SDRAM controlle.*

*• They have been developed with Diab Data compiler and are executed under Lauterbach debugger.*

*A more detailed course description is available on request at [formation@ac6-formation.com](mailto:formation@ac6-formation.com)*

### Prerequisites and related courses

- Experience of a 32-bit processor or DSP is mandatory.
- Knowledge of PCI is mandatory, see our course reference [IC1 - PCI 3.0](#)course

### Course Environment

- Theoretical course
  - PDF course material (in English) supplemented by a printed version for face-to-face courses.
  - Online courses are dispensed using the Teams video-conferencing system.
  - The trainer answers trainees' questions during the training and provide technical and pedagogical assistance.
- At the start of each session the trainer will interact with the trainees to ensure the course fits their expectations and correct if needed

### Target Audience

- Any embedded systems engineer or technician with the above prerequisites.

### Evaluation modalities

- The prerequisites indicated above are assessed before the training by the technical supervision of the trainee in his company, or by the trainee himself in the exceptional case of an individual trainee.
- Trainee progress is assessed by quizzes offered at the end of various sections to verify that the trainees have assimilated the points presented
- At the end of the training, each trainee receives a certificate attesting that they have successfully completed the course.
  - In the event of a problem, discovered during the course, due to a lack of prerequisites by the trainee a different or additional training is offered to them, generally to reinforce their prerequisites, in agreement with their company manager if applicable.

## Plan

### INTRODUCTION TO THE MPC824X

- Internal data paths, CCU operation
- Benefits of the snooper, sharing of cache enabled regions
- Mapping detail

### ADDRESS TRANSLATION

- Address translation from core to PCI Memory space
- Address translation from PCI to SDRAM
- Selection of the base address of internal memory mapped status and control registers

### RESET SEQUENCE

- Self configuration of the MPC824X through input sampling
- Requirements of the boot routine

### THE PPC603e CORE

- 603e pipeline introduction
- instruction queue, superscalar execution, register renaming, out-of-order execution
- Dispatch conditions, completion conditions
- FPU and LSU internal pipeline operation
- Execution serialization
- Branch management : static prediction
- Guarded memory

### L1 CACHES

- Cache basics
- Cache related page / block attributes
- 603e L1 cache : LRU algorithm, HID0 programming interface
- Software L1 data cache flush
- Cache coherency : the MEI 3-bit L1 data line state
- MEI snooping sequences involving the 603e core and a PCI master

### THE UISA LAYER

- Branch instructions
- Integer load / store instructions, boolean semaphore management
- Integer arithmetic and logic instructions
- IEEE754 basics
- FPU operation
- The EABI
- Code and data sections, small data areas benefits

### THE VEA LAYER

- Cache related instructions
- PowerPC timers : TB and DEC

### THE OEA LAYER - MMU

- MMU goals
- The PowerPC address processing : real mode, bloc address translation, segment / page mode
- WIMG attributes definition

- Process protection through VSID selection
- TLB organization
- Page translation
- MMU implementation in real-time sensitive applications

## **THE OEA LAYER - EXCEPTION MECHANISM**

- Exception state saving and restoring
- Exception management
- Recoverable vs non recoverable interrupts
- Requirements to support exception nesting

## **INTEGRATED DEBUG FACILITIES**

- Tagging of the master accessing SDRAM
- Hardware vs software breakpoint
- JTAG emulation
- Real time trace requirements

## **HARDWARE IMPLEMENTATION**

- Pinout
- Clocking, selection of the PLL ratio
- DLL benefit, electrical interface

## **THE MEMORY CONTROLLER**

- SDRAM basics, page mode, refresh, timing diagrams
- SDRAM related registers initialisation according to IBM SDRAM device features
- The Flash EPROM controller
- Port-X

## **THE PCI INTERFACE**

- Commands supported when the bridge is a PCI master and when the bridge is a PCI target
- Access to the local SDRAM address space by a PCI master
- Generation of configuration transactions

## **INTERNAL PERIPHERALS**

- The interrupt controller
- Internal timers
- Synchronization mechanisms : doorbell registers, I2O compliant messaging
- The DMA controller, selection of the command generated on the PCI side
- The I2C controller

## **Renseignements pratiques**

**Inquiry : 5 days**