



RA2 - Cortex-A9 implementation

This course covers both Cortex-A9 single and multiple core high-end ARM CPUs

Objectives

- This course is split into 3 important parts:
 - Cortex-A9 architecture
 - Cortex-A9 software implementation and debug
 - Cortex-A9 hardware implementation
- MMU operation under Linux is described.
- Spin-lock implementation in a multicore system is also detailed
- Interaction between level 1 caches, level 2 cache and main memory is studied through sequences.
- The exception mechanism is explained, indicating how virtualization enables the support of several operating systems.
- The course also details the hardware implementation and provides some guidelines to design a SoC based on Cortex-A9.
- An overview of the Coresight specification is provided prior to describing the debug related units.
- The operation of the Snoop Control Unit when supporting SMP is fully explained, particularly the utilization of cache tag mirrors, the advantage of connecting DMA channels to ACP and the sequences that have to be used to modify a page descriptor.

Labs are run under RVDS.

A more detailed course description is available on request at info@ac6-training.com

Prerequisites and related courses

- Knowledge of ARM7/9 or having attended our course ARM fundamentals.
- This course does not include chapters on low level programming.
 - ACSYS offers a large set of tutorials to become familiar with RVDS, assembly level programming, compiler hints and tips.
- More than 12 correct answers to our Cortex-A prerequisites questionnaire.
- Related courses:
 - Programming with RVDS IDE, reference [RV0](#)
 - VFP programming, reference [RC0](#)
 - NEON programming, reference [RC1](#)

Plan

First day

INTRODUCTION TO CORTEX-A9

- Cortex-A9 variants
- New memory-mapped registers in MPCore
- The 3 instruction sets
- Configurable options

ARM BASICS

- States and modes
- Benefit of register banking
- Exception mechanism
- Instruction sets

INSTRUCTION PIPELINE

- Superscalar pipeline operation
- Branch prediction mechanism
- Return stack
- Predicted and non-predicted instructions

TRUSTZONE

- Secure to non secure permitted transitions
- L1 and L2 secure state indicators, memory partitioning
- Interrupt management when there is a mix of secure and non-secure interrupt sources
- Boot sequence

INTRODUCTION TO MULTI-CORE SYSTEMS

- AMP vs SMP
- Boot sequence
- Exclusive access monitor
- Spin-lock implementation
- Using events
- Basic concepts of RTOS supporting A9 SMP architecture

Second day

THUMB-2 INSTRUCTION SET (V7-A)

- General points on syntax
- Branch and control flow instructions
- Memory access instructions
- Exception generating instructions
- If-then conditional blocks
- Interworking ARM and Thumb states

- Demonstration of assembly sequences aimed to understand this new instruction set

MEMORY MANAGEMENT UNIT

- Page access permission, domain and page protection
- Page attributes, memory types
- Utilization of memory barrier instructions
- Format of the external page descriptor table
- TLB lockdown
- Abort exception, on-demand page mechanism
- MMU maintenance operations
- Using a common page descriptor table in an SMP platform, maintaining coherency of multiple TLBs

LEVEL 1 MEMORY SYSTEM

- Virtual indexing, physical tagging for instruction cache
- Supported maintenance operations
- Write-back write allocate cache allocation
- Memory hint instructions PLD, PLI, PLDW, data prefetching
- Describing transient cache related transactions: line fills and line eviction
- 4-entry 64-bit merging store buffer

HARDWARE COHERENCY

- Snooping basics: CLEAN, CLEAN & INVALIDATE and INVALIDATE snoop requests
- Snoop Control Unit: cache-to-cache transfers
- MOESI state machine
- Understanding through sequences how data coherency is maintained between L2 memory and L1 caches
- Accelerator Coherency Port

Third day

AMBA 3

- AXI
 - Topology: direct connection, multi-master, multi-layer
 - PL301 AXI interconnect
 - Separate address/control and data phases
 - AXI channels, channel handshake
 - Transaction ordering
 - Read and write burst timing diagrams
 - Cortex-A9 external memory interface, ID encoding
- APB 3

HARDWARE IMPLEMENTATION

- Clock domains
- Reset domains
- Wait For Interrupt architecture
- AXI master interface attributes
- Exclusive L2 cache
- AXI sideband information

PL310 LEVEL 2 CACHE

- AXI interface characteristics

- Exclusive mode operation
- Understanding through sequences how cacheable information is copied from memory to level 1 and level 2 caches
- TrustZone support
- Power management
- Cache event monitoring
- Describing each maintenance operation
- Cache lockdown
- Interrupt management

PERFORMANCE MONITOR

- Event counting
- Selecting the event to be counted for the 6 counters
- Debugging a multi-core system with the assistance of the PMU

Fourth day

INTERRUPT CONTROLLER

- Cortex-A9 exception management
- Interrupt virtualization
- Integrated timer and watchdog unit in MPCore
- Interrupt groups: STI, PPI, SPI, LSPI
- Legacy mode
- Prioritization of the interrupt sources
- Distribution of the interrupts to the Cortex-A9 cores
- Detailing the interrupt sequence
- Spurious interrupt

LOW POWER MODES

- Voltage domains
- Cortex-A9 power control
- Communication to the power management controller
- SCU power status register

CORESIGHT DEBUG UNITS

- Invasive debug, non-invasive debug
- APBv3 debug interface
- Connection to the Debug Access Port
- Process related breakpoint and watchpoint
- Program counter sampling
- Event catching
- Debug Communication Channel
- PTM interface, connection to funnel
- Debug registers description
- Cross-Trigger Interface, debugging a multi-core SoC

Renseignements pratiques

Durée : 4 jours

Prix : 1950 € HT



SARL au capital de 15400€ - SIRET 449 597 103 00026 - RCS Nanterre - NAF 722C - Centre de Formation : 19, rue Pierre Curie - 92400 Courbevoie
Siège social et administration : 21, rue Pierre Curie - 92400 Courbevoie - Tél. 01 41 16 80 10 - Fax. 01 41 16 07 78

Dernière mise à jour du site: lun 21 mai 2012 17:28:46 CEST

<http://www.ac6-formation.com/>