



FM4 - MPC5200 implementation

This course covers the MPC5200 Freescale MCU

Objectives

- The course explains how to design a MPC5200 board.
- DDR SDRAM operation is described in order to understand the memory controller programming.
- The 603e core is studied in detail, especially the MMU.
- The course provides examples of internal peripherals software drivers.
- Fast Ethernet controller is viewed in detail.
- The training highlights data paths between PCI and DDR SDRAM.
- This course has been delivered several times to companies developing embedded multimedia equipments.

A lot of programming examples have been developed by ACSYS to explain the boot sequence and the operation of complex peripherals, such as BestComm and Fast Ethernet.

-They have been developed with Diab Data compiler and are executed under Lauterbach debugger.

A more detailed course description is available on request at info@ac6-training.com

Prerequisites and related courses

- Experience of a 32-bit processor or DSP is mandatory.
- The following courses could be of interest:
 - Ethernet and switching, reference [N1](#)
 - PCI, reference [IC1](#)
 - USB Full Speed High Speed and USB On-The-Go, reference [IP2](#)

Plan

INTRODUCTION TO MPC5200

Overview

- Innovative IO subsystem
- Dual external bus architecture : SDRAM bus and LocalPlus bus
- Bestcomm features
- Memory map, internal register space

PROCESSOR CORE

603e CORE

- 603e pipeline
- Branch management : static prediction
- Guarded memory
- 603e L1 cache : LRU algorithm, HID0 programming interface
- Software L1 data cache flush
- Cache coherency basics
- JTAG debugger, hardware breakpoint vs software breakpoints
- Branch instructions
- The system call communication path between applications and RTOS
- FPU operation
- The EABI
- Code and data sections, small data areas benefits
- Cache related instructions
- PowerPC timers : TB and DEC
- MMU goals
- The PowerPC address processing
- WIMG attributes definition, page and block access rights definition
- Process protection through VSID selection
- TLB organization, TLB software management
- MMU implementation in real-time sensitive applications
- Exception management
- Requirements to support exception nesting

PLATFORM

SYSTEM INTEGRATION UNIT

- Interrupt Controller routing scheme
- General purpose IO, pin multiplexing
- General purpose Timers
- Slice timers, generation of periodic interrupts
- · Real-Time Clock

HARDWARE IMPLEMENTATION

- Reset configuration
- Clock domains
- Power management
- DDR SDRAM basics
- The DDR SDRAM controller, pinout
- Power-up initialisation, use of the I2C interface
- Initialization of memory controller registers according to a micron DDR SDRAM devices
- External bus interface, modes of operation muxed or non muxed
- Connection to ATA and PCI compliant devices as well as memory-mapped devices
- Chip select programming
- Dynamic bus sizing
- DMA interface
- XLB arbiter, prioritisation, bus grant mechanism

BESTCOMM

- SmartDMA modules, local buffer memory
- Servicing many data streams with individual latency and processing requirements
- Chaining scatter / gather capability
- Task descriptor table
- Function descriptor table

PCI CONTROLLER

- Supported clock ratios
- PCI commands supported as a target and as a master
- XL bus initiator interface
- Endian translation
- XL bus target interface
- Multi-channel DMA transmit interface
- Multi-channel DMA receive interface
- Access to the configuration space
- Programming of inbound and outbound windows
- PCI agent vs PCI host operation mode

INTEGRATED I/Os**USB CONTROLLER**

- Data transfer types
- Host Controller interface
- OHCI specification, communication channels
- Root hub partition

CAN CONTROLLER

- The MSCAN controllers, clock system
- Message buffers structure
- ID bit masking
- Arbitration
- Timing and synchronization
- Error management
- Interrupt driven operation

SPI CONTROLLER

- Baud rate selection, transfer delays
- Double-buffered operation
- Transmit and receive sequences

ATA CONTROLLER

- Asynchronous ATA basics, overview of ATA standards
- ATA host controller operation
- Signals and connections
- Sector addressing
- Ultra DMA protocol

FAST ETHERNET CONTROLLER

- MII transfers
- FIFO interface
- Address recognition
- Full and half duplex operation
- Initialization sequence
- MIB block counters

PROGRAMMABLE SERIAL CONTROLLERS

- PSC in UART mode
- PSC in Codec mode
- PSC in AC97 mode
- PSC in Infrared SIR, MIR or FIR mode
- FIFO system

I2C CONTROLLER

- I2C protocol basics
- Transfer timing diagrams, SCL and SDA pins
- Clock synchronization and arbitration
- Transmit and receive sequences

Renseignements pratiques

Duration : 5 days
Cost : 2100 € HT



SARL au capital de 15400€ - SIRET 449 597 103 00026 - RCS Nanterre - NAF 722C - Centre de Formation : 19, rue Pierre Curie - 92400 Courbevoie
Siège social et administration : 21, rue Pierre Curie - 92400 Courbevoie - Tél. 01 41 16 80 10 - Fax. 01 41 16 07 78

Last site update: Tue 22 May 2012 10:50:29 AM CEST

<http://www.ac6-formation.com/>