



MV2 - MARVELL MV64560 implementation

This course covers Marvell Discovery V devices

Objectives

- The course describes the MV64560 internal data paths.
- The course explains how the host PowerPC and a CPU connected to PCI-X can synchronize to each other through the message unit.
- Operation of the PCI Express interface is detailed in Root Complex mode as well as in Endpoint mode.
- A long introduction to DDR SDRAM is done prior to describe the DDR SDRAM controller operation.
- The course focuses on the hardware implementation of the DDR SDRAM.
- The training explains how to implement chained DMA transfers, by using either IDMA channels or XOR engines.
- The course highlights the possible optimizations that can be implemented to boost the performance of the Ethernet controller.
- This course has been delivered several times to companies developing defence and avionics systems.

A more detailed course description is available on request at info@ac6-formation.com

Pre-requisites

- Knowledge of PowerPC 60X / MPX bus. See our courses on Freescale and IBM Microelectronics PowerPCs.

Related courses

- Ethernet and switching, reference [N1](#)
- PCI express, reference [IC4](#)
- USB Full Speed High Speed and USB On-The-Go, reference [IP2](#)

Plan

OVERVIEW

- 5-bus architecture, organization of a board based on MV64560
- Frequency domains, fast path between CPU and SRAM / SDRAM
- Internal crossbar
- Master de-mux programming, address decode windows
- Slave mux programming, pizza arbiters operation
- Compatibility with MV64460

CPU INTERFACE

- CPU address space decoding

- Protection windows
- Arbitration, multi-processor operation
- CPU slave operation
- CPU master operation (60X mode)
- Cache coherency
- Deadlock avoidance

DDR1/2 INTERFACE

- Introduction to DDR SDRAM from Jedec specification
- Differences between DDR1 and DDR2
- DDR2 on-die terminations
- Initialization sequence
- DDR1/2 SDRAM controller
- Page management
- Transaction ordering
- Cache coherency
- ECC and read-modify-write transactions
- Low power modes

DEVICE CONTROLLER

- Functional description
- Address and data multiplexing
- Connecting 8/16 bit devices
- External acknowledgement
- Pack / unpack and burst support
- NAND flash support, boot from NAND flash

PCI INTERFACE

- PCI bus arbitration
- Master operation in PCI and PCI-X mode
- Target operation in PCI and PCI-X mode
- PCI-to-PCI configuration transactions
- Address decoding

PCI-EXPRESS x4 INTERFACE

- Integrated low power SERDES PHY
- x1, x4 link
- Operating as either Root Complex or Endpoint
- Link initialization
- Arbitration and ordering
- Messaging unit

GENERAL PURPOSE INPUT/ OUTPUT PINS

- GPIO port, functional description
- Interrupt request inputs
- Multi Purpose Pin multiplexing

INTERRUPT CONTROLLERS AND TIMERS

- Timers / counters
- Interrupt controller functional description
- Priority mechanism

TWSI CONTROLLER AND RESET

- I2C protocol basics
- TWSI controller functional description
- Master write sequence, master read sequence
- Slave write sequence, slave read sequence
- Reset pins and configuration
- Serial ROM initialization
- Requirement for an external Central Resource CPLD

IDMA CHANNELS

- IDMA address decoding
- Target unit and attributes programming
- Normal mode vs chained mode
- Transfer descriptors, descriptor ownership
- DMA interrupts

XOR ENGINES

- State machine : Active, Inactive and Paused states
- XOR operation mode
- CRC32 operation mode
- DMA operation mode
- Memory Initialization operation mode
- ECC error cleanup operation mode
- XOR Engines interrupts

16550 COMPATIBLE UARTs

- FIFO mode
- Flow control
- Transmit sequence
- Receive sequence

USB2.0 PORTS

- Address decoding
- Integrated PHY
- USB host operation, EHCI specification support
- USB device operation, Endpoint configuration

GIGABIT ETHERNET CONTROLLERS

- Interface to the PHY
- SGMII support
- Dedicated DMA
- Transmit weighted round-robin arbitration
- Backpressure mode
- Transmit and receive sequences
- Management interface
- Synchronous FIFO interface

Renseignements pratiques

Duration : 4 days
Cost : 1950 € HT



SARL au capital de 15400€ - SIRET 449 597 103 00026 - RCS Nanterre - NAF 722C - Centre de Formation : 19, rue Pierre Curie - 92400 Courbevoie
Siège social et administration : 21, rue Pierre Curie - 92400 Courbevoie - Tél. 01 41 16 80 10 - Fax. 01 41 16 07 78

Last site update: Tue 22 May 2012 10:50:29 AM CEST

<http://www.ac6-formation.com/>