



MV3 - MARVELL MV64660 implementation

This course covers Marvell Discovery VI devices

Objectives

- The course describes the MV64660 internal data paths.
- The course explains how the host PowerPC and a CPU connected to PCI-X can synchronize to each other through the message unit.
- Operation of the PCI Express interface is detailed in Root Complex mode as well as in Endpoint mode.
- A long introduction to DDR SDRAM is done prior to describe the DDR SDRAM controller operation.
- The course focuses on the hardware implementation of the DDR SDRAM.
- The training explains how to implement chained DMA transfers, by using either IDMA channels or XOR engines.
- The course highlights the possible optimizations that can be implemented to boost the performance of the Ethernet controller.

A more detailed course description is available on request at info@ac6-formation.com

Pre-requisites

- Knowledge of PowerPC 60X / MPX bus. See our courses on Freescale and IBM Microelectronics PowerPCs.

Related courses

- Ethernet and switching, reference [N1](#)
- PCI express, reference [IC4](#)
- USB Full Speed High Speed, reference [IP2](#)
- Serial-ATA, reference [IS3](#)

Plan

OVERVIEW

- 6-bus architecture, organization of a board based on MV64660
- Frequency domains, fast path between CPU and SRAM / SDRAM
- Data integrity checking
- Internal crossbar
- Master de-mux programming, address decode windows
- Slave mux programming, pizza arbiters operation

CPU INTERFACE

- CPU address space decoding

- CPU-to-PCI address remapping
- Protection windows
- Arbitration, multi-processor operation
- CPU slave operation
- Cache coherency
- Deadlock avoidance
- Transaction ordering
- Hardware implementation, clocking, low power modes

DDR2 INTERFACE

- Introduction to DDR SDRAM from Jedec specification
- DDR2 on-die terminations
- Clocking
- Initialization sequence
- Data synchronization : DQS signals, programmable DLL
- DDR2 SDRAM controller, functional description
- Page management
- Read and write transactions
- ECC and read-modify-write transactions
- Hardware implementation, ODT management (internal and external)
- Low power modes

DEVICE CONTROLLER

- Transaction queue, read and write data buffers
- Address and data multiplexing
- Timing parameters
- External acknowledgement
- Pack / unpack and burst support
- NAND flash support, boot from NAND flash

PCI INTERFACE

- PCI bus arbitration
- Master operation in PCI and PCI-X mode
- Target operation in PCI and PCI-X mode
- PCI-to-PCI configuration transactions
- Address decoding

PCI-EXPRESS x4 AND x1 INTERFACES

- Integrated low power SERDES PHY
- x1, x4 link
- Operating as either Root Complex or Endpoint
- Link initialization
- Arbitration and ordering
- Peer-to-peer traffic
- Messaging unit, synchronization between CPUs through PCI/PCI-Express

GENERAL PURPOSE INPUT/ OUTPUT PINS

- GPIO port, functional description
- Interrupt request inputs
- Multi Purpose Pin multiplexing

INTERRUPT CONTROLLERS AND TIMERS

- Watchdog timer
- Interrupt controller functional description
- Interrupt steering logic to 4 possible output pins
- Priority mechanism

TWSI CONTROLLER AND RESET

- Master and slave operation, 7- or 10-bit addressing
- Determining the current state of the controller by reading the status register
- Master write sequence, master read sequence
- Slave write sequence, slave read sequence
- Reset pins and configuration
- Utilization of the boot sequencer
- Requirement for an external Central Resource CPLD

IDMA CHANNELS

- IDMA address decoding
- Target unit and attributes programming
- Functional description, external control
- Normal mode vs chained mode
- Transfer descriptors, descriptor ownership
- Channel activation
- DMA interrupts

XOR ENGINES

- State machine : Active, Inactive and Paused states
- XOR, CRC and DMA operation modes, format of transfer descriptors
- XOR operation mode
- CRC32 operation mode
- DMA operation mode
- Memory Initialization operation mode
- ECC error cleanup operation mode
- Arbitration between XOR engine0 and XOR engine1
- Address override capability
- XOR Engines interrupts

16550 COMPATIBLE UARTs

- FIFO mode
- Flow control
- Transmit sequence
- Receive sequence

USB2.0 PORTS

- Address decoding
- Integrated PHY
- USB host operation, EHCI specification support
- USB device operation, Endpoint configuration
- Dedicated DMA for data movement between memory and port

SATA-II INTERFACE

- Integrated PHY, 3.0 or 1.5 Gbps bit rate
- EDMA request and response queues
- Studying the sequence that the software must implement to perform a PIO transfer
- Studying the sequence that the software must implement to perform a DMA transfer
- Queued DMA
- Interrupt coalescing
- Port multiplier support

GIGABIT ETHERNET CONTROLLERS

- SGMI support
- Dedicated DMA
- Related interrupts
- Transmit weighted round-robin arbitration
- Backpressure mode
- Transmit and receive sequences
- Management interface
- MIB

CRYPTOGRAPHIC ENGINE AND SECURITY ACCELERATORS

- Cryptographic engine functional description
- Involved units : CPU, dedicated SRAM and security accelerator
- Authentication
- Encryption and decryption, supported algorithms
- TDMA controller, attaching TDMA to security accelerator
- Multi-packet chained mode
- DES encryption / decryption sequence, pipelining

Renseignements pratiques

Duration : 5 days
Cost : 2100 € HT

