

FPQ6 - MPC8313E implementation

This course covers PowerQUICC II Pro MPC8313

Objectives

- The course focuses on the sequencer that interconnects e300, DDR SDRAM, PCI and external bus.
- Cache coherency protocol is introduced in increasing depth.
- The 32-bit e300 core is viewed in detail, especially the MMU and the cache.
- The boot sequence and the clocking are explained.
- The course focuses on hardware implementation of the MPC8313E.
- A long introduction to DDR SDRAM operation is done before studying the DDR2 SDRAM controller.
- An in-depth description of the PCI controllers is performed.
- The course highlights both hardware and software implementation of gigabit / fast / Ethernet controllers.
- The USB interfaces are also detailed.
- Generation of a Linux image and Root File System by using LTIB can also be included into the training.

A lot of programming examples have been developed by ACSYS to explain the boot sequence and the operation of complex peripherals, such as USB and Ethernet.

• They have been developed with Diab Data compiler and are executed under Lauterbach debugger.

A more detailed course description is available on request at formation@ac6-formation.com

Prerequisites and related courses

- The knowledge of the following interconnect standards may be required:
 - PCI, see our course reference [IC1 - PCI 3.0](#) course
 - Gigabit Ethernet, see our course reference [N1 - Ethernet and switching](#) course
 - USB 2.0, see our course reference [IP2 - USB 2.0](#) course

Course Environment

- Theoretical course
 - PDF course material (in English) supplemented by a printed version for face-to-face courses.
 - Online courses are dispensed using the Teams video-conferencing system.
 - The trainer answers trainees' questions during the training and provide technical and pedagogical assistance.
- At the start of each session the trainer will interact with the trainees to ensure the course fits their expectations and correct if needed

Target Audience

- Any embedded systems engineer or technician with the above prerequisites.

Evaluation modalities

- The prerequisites indicated above are assessed before the training by the technical supervision of the trainee in his company, or by the trainee himself in the exceptional case of an individual trainee.
- Trainee progress is assessed by quizzes offered at the end of various sections to verify that the trainees have assimilated the points presented
- At the end of the training, each trainee receives a certificate attesting that they have successfully completed the course.

- In the event of a problem, discovered during the course, due to a lack of prerequisites by the trainee a different or additional training is offered to them, generally to reinforce their prerequisites, in agreement with their company manager if applicable.

Plan

INTRODUCTION TO MPC8313E

Overview

- Enhancements compared to MPC824X
- Memory map
- Block diagram
- Application examples

THE e300 CORE

THE INSTRUCTION PIPELINE

- Pipeline
- Branch processing unit
- Simplified branch mnemonics
- Coding guidelines

DATA PATHS

- Load / store buffers
- Sync and eieio instructions
- Store gathering mechanism

CACHES

- Cache basics
- Relationship between cache and burst, critical word first order
- L1 caches
- Shared resource management
- Cache coherency mechanism
- Management of cache enabled pages shared with PCI DMAs
- Cache related instructions
- Cache flush routine

SOFTWARE IMPLEMENTATION

- PowerPC architecture specification, the 3 books UISA, VEA and OEA
- Addressing modes, load / store instructions
- Integer instructions
- Rotate instructions : inserting and extracting bitfields
- IEEE754 basics, floating points numbers encoding
- Floating point arithmetical instructions
- The PowerPC EABI
- Linking an application with Diab Data, parameterizing the linker command file

THE MMU

- Thread vs process
- Introduction to real mode, block and segmentation / pagination translations
- Real mode restrictions

- Memory attributes and access rights definition
- Virtual space benefit, page protection through segmentation
- TLBs organization
- PTE table organization, tablesearch algorithm
- MMU implementation in real-time sensitive applications

THE EXCEPTION MECHANISM

- Save / restore registers SRR0/SRR1, rfi instruction
- Exception management mechanism
- Registers updating according to the exception cause
- Requirements to allow exception nesting

THE DEBUG PORT

- JTAG emulation, restrictions
- Code instrumentation
- Hardware breakpoints

THE PLATFORM CONFIGURATION

POWER, RESET AND CLOCKING

- DC and AC electrical characteristics
- Reset causes
- Configuration signals sampled at reset
- Reset configuration words source, boot from I2C or boot from EEPROM
- PCI Host / Agent configuration
- Clocking in PCI Host mode, system clock domains
- System PLL ratio
- Delay Locked Loop

ADDRESS TRANSLATION AND MAPPING

- Local memory map
- Local access windows
- Distinguishing Local Access Windows from other mapping functions
- Inbound and outbound windows definition

ARBITER AND BUS MONITOR

- External signal description
- PCI outbound window definition
- Transaction forwarding

SEQUENCER

- Coherent system bus overview
- Arbitration policy
- Bus error detection

GENERAL PURPOSE INPUTS / OUTPUTS

- Pin model
- Interrupt inputs

THE DDR2 MEMORY CONTROLLER

- DDR-SDRAM operation : a 128-Mbits DDR-SDRAM from Micron is used as an example

- Jedec specification basics
- Differences between DDR1 and DDR2
- Command truth table
- Refresh types
- Bank activation, read, write and precharge timing diagrams, page mode
- ECC error correction
- DDR-SDRAM controller overview
- Initial configuration following Power-on-Reset
- Address decode
- Timing parameters programming
- Initialization routine

LOCAL BUS CONTROLLER

- Multiplexed or non-multiplexed address and data buses
- Dynamic bus sizing
- GPCM, UPMs states machines
- Interfacing to ZBT SRAMs
- Interfacing to DSP host ports
- NAND flash controller

PCI BUS INTERFACE

- Bridge features
- Data flows : Read prefetch and write posting FIFOs
- Inbound transactions handling, Outbound transactions handling
- PCI bus arbitration
- PCI hierarchy configuration when operating as host

INTEGRATED DMA CONTROLLER

- Priority between the 4 channels
- Support for cascading descriptor chains
- Concurrent execution across multiple channels with programmable bandwidth control
- Messaging unit
- Doorbells management

INTEGRATED PROGRAMMABLE INTERRUPT CONTROLLER

- Interrupt masking
- Definition of interrupt priorities
- System critical interrupt
- Requirements to support nesting

TIMERS

- Software watchdog timer
- Real time clock module
- Periodic Interval Timer
- General Purpose Timers

INTEGRATED PERIPHERALS

SECURITY ENGINE [optional, MPC8313E only]

- Overview of the encryption mechanism
- Introduction to DES and 3DES algorithms
- Data packet descriptors
- Crypto channels

THE ETHERNET CONTROLLERS

- 802.3 specification fundamentals
- MAC address recognition, 256-entry hash table for unicast and multicast
- Interface with the PHY (SGMII)
- Buffer descriptors management
- Flow control
- Level 2, 3 and 4 hardware acceleration mechanisms (TCP/IP Offload Engine)
- Quality of service support
- Hardware assist for IEEE1588 support

THE USB 2.0 CONTROLLER

- Dual-role (DR) operation
- EHCI implementation
- UTMI / ULPI interfaces to the transceiver
- OTG support
- Dedicated DMA channels
- Endpoints configuration

LOW SPEED PERIPHERALS

- Description of the NS16450/16550 compliant Uarts
- Flow control signal management
- I2C protocol fundamentals
- Transmit and receive sequence
- SPI protocol basics
- Master vs slave operation

Linux Target Image Builder (LTIB)

GENERATING THE LINUX KERNEL IMAGE

- Introducing the tools required to generate the kernel image
- What is required on the host before installing LTIB
- Common package selection screen
- Common target system configuration screen
- Building a complete BSP with the default configurations
- Creating a Root Filesystems image
- e-configuring the kernel under LTIB
- Selecting user-space packages
- Setup the bootloader arguments to use the exported RFS
- Debugging Uboot and the kernel by using Trace32
- Command line options
- Adding a new package
- Other deployment methods
- Creating a new package and integrating it into LTIB
 - A lot of labs have been created to explain the usage of LTIB

Renseignements pratiques

Duration : 5 days
Cost : 2100 € HT